

ES2.9-12



SPECIFICATIONS

Nominal Voltage (V)	12V
Nominal Capacity	
20hour rate (0.145A to 10.50V)	2.9Ah
10hour rate (0.29A to 10.50V)	2.9Ah
5hour rate (0.493A to 10.20V)	2.465Ah
1C (2.9A to 9.60V)	1.305Ah
3C (8.7A to 9.60V)	1.044Ah
Weight	2.59 Lbs. (1.176 kg)
Internal Resistance (at 1KHz)	33 mΩ
Maximum Discharge Current for 30 seconds :	58A
Maximum Discharge Current for 5 seconds :	116A
Operating Temperature Range	
Charge	0°C(32°F) to 40°C (104°F)
Discharge	-15°C(5°F) to 50°C (122°F)
Storage	-15°C(5°F) to 40°C (104°F)
Charge Retention (shelf life) at 20°C (68°F)	
1 month	92%
3 month	90%
6 month	80%
Charging Methods at 25°C (77°F)	
Cycle use :	Charging Voltage 14.4 to 15.0V Maximum Charging Current 0.87A
Standby use :	Float Charging Voltage 13.50 to 13.80V No current limit required
Life expectancy :	
Cycle Use :	100% depth of discharge 250 cycles 80% depth of discharge 350 cycles 50% depth of discharge 550 cycles
Standby Use :	3-5 years
Case Material	ABS (94-HB & 94V-0 flame retardant case)
Terminal	F1

Maintenance-Free Rechargeable Sealed Lead-Acid Battery



DIMENSIONS



MK Battery

1645 South Sinclair Street • Anaheim, California 92806
Toll Free: 800-372-9253 • Fax: 714-937-0818 • E-Mail: sales@mkbattery.com

