

# 8A4DLTP-DEKA

## SPECIFICATIONS

Nominal Voltage (V)	12V
Capacity at C/100	210Ah
Capacity at C/20	198Ah
Weight	133.5 lbs. (61 kg)
Plate Alloy	Lead Calcium
Posts	Forged Terminals & Bushings
Container/Cover	Polypropylene
Operating Temperature Range	-40°F (-40°C) - 140°F (60°C)

For Charging Parameters please refer to [www.mkbattery.com](http://www.mkbattery.com)

Click on Technical Data, then on Photovoltaic Charging Parameters in the PV/Solar section

Vent Self-sealing

Terminal T (T975)



Rated UN2794 - Wet, Filled with Acid

Made in the U.S.A. by East Penn Manufacturing Co., Inc.

Distributed by:

## Valve-Regulated, Absorbed Glass Mat Technology



## DIMENSIONS


Inches (mm)

Length 20.73 (527 mm)  
Including handles

Width 8.44 (214 mm)

Height 10.82 (275 mm)  
Including terminals

AGM Cycle Life vs. Depth of Discharge at +25°C (77°F)  
Based on BCI 2-hour Capacity



**MK Battery**

1631 South Sinclair Street • Anaheim, California 92806

Toll Free: 800-372-9253 • Fax: 714-937-0818 • E-mail: [sales@mkbattery.com](mailto:sales@mkbattery.com)

